

Tree Watch Parking vehicle SWMS 10

Names of staff that have read and understand this SWMS: **Stephen Bayley, Angus Cullenward, Daniel Bayley, Ashley Morrison, David Smith**

When parking a vehicle it is essential that the vehicle is correctly parked and will not roll away.

The consequence of a vehicle rolling away are lethal and multiple people could be killed in extreme circumstances.

At Tree Watch the steps to complete when parking include;

Park the vehicle in the safest and most practical location to complete the job.

Leave the car in first gear.

Turn the wheel full to the kerb.

Apply the handbrake firmly.

If on a steep gradient or if there are any doubt about whether the vehicle is secure get a passenger to install at least two wheel chocks and up to five depending on the steepness of the location and weight on board, chipper etc.

Let go of everything and make sure the vehicle is secure.

If in doubt don't do it, move the vehicle to a safer location.

Failure to apply this procedure will result in disciplinary action.

The persons (employees, subcontractors and others) that have sent back there digital signatures have:

1. been involved in the hazard/risk assessment and the determination of the hazard/risk controls applicable to their tasks, duties and responsibilities
2. had all hazards and risk controls have been communicated to them
3. and are fully aware of and understand the hazards/risks and safety risk controls and rules required
4. agreed to all the hazard/risk controls
5. agreed to and understand their Duty of Care to themselves and others
6. agreed that they are the person responsible for site supervision of the work, inspecting and approving work areas, work methods, compliance with SWMS, protective measures, plant, equipment and power tools.

